AGRI

UNIVERSAL OILS FOR AGRICULTURAL AND CONSTRUCTION MACHINERY







AVANTGARDE

LUKOIL AVANTGARDE 10W LUKOIL AVANTGARDE 20W-20 LUKOIL AVANTGARDE 30 LUKOIL AVANTGARDE ULTRA PLUS 10W-40 LUKOIL AVANTGARDE EXTRA 15W-40 LUKOIL AVANTGARDE ULTRA 20W-50 LUKOIL AVANTGARDE ULTRA 15W-40 LUKOIL AVANTGARDE PROFESSIONAL LA 10W-30 LUKOIL AVANTGARDE PROFESSIONAL LA 10W-40 LUKOIL AVANTGARDE PROFESSIONAL LA 15W-40 TRANSMISSION LUKOIL TRANSMISSION LS 80W-90 LUKOIL TRANSMISSION LS 85W-90 LUKOIL TRANSMISSION B 80W-90 LUKOIL TRANSMISSION MP 80W-85 LUKOIL TRANSMISSION MP 85W-90 LUKOIL TRANSMISSION UNI 80W-90 VERSO LUKOIL VERSO MOTOR 10W-40 LUKOIL VERSO MOTOR 15W-40 LUKOIL VERSO MOTOR 15W-30 LUKOIL VERSO HGN LUKOIL VERSO STE LUKOIL VERSO NPS GEYSER LUKOIL GEYSER ST 22 LUKOIL GEYSER ST 32 LUKOIL GEYSER ST 46 LUKOIL GEYSER ST 46 LUKOIL GEYSER ST 68	7 8 9
LUKOIL TRANSMISSION LS 85W-90	
	4.0
20.00.2	10
LUKOIL TRANSMISSION UNI 80W-90	11
VERSO	
LUKOIL VERSO MOTOR 15W-40 LUKOIL VERSO MOTOR 15W-30 LUKOIL VERSO HGN LUKOIL VERSO LVX LUKOIL VERSO STE	13
GEYSER	
LUKOIL GEYSER ST 32 LUKOIL GEYSER ST 46 LUKOIL GEYSER ZF 46	4.6
LUKOIL GEYSER ST 68 LUKOIL GEYSER M 32	16
LUKOIL GEYSER M 46 LUKOIL GEYSER M 68 LUKOIL GEYSER BIO S 32 LUKOIL GEYSER BIO S 46	17
LUKOIL CHAIN MEDIUM LUKOIL CHAIN HEAVY LUKOIL BIOCHAIN LIGHT	
LUKOIL BIOCHAIN MEDIUM LUKOIL BIOCHAIN HEAVY	
LUKOIL BIOSEGAROL E 100	18

LUKOIL LUBRICANTS ENABLE RELIABLE MOBILITY FOR MILLIONS WORLDWIDE AND PROVE THEMSELVES DAILY UNDER ALL CONDITIONS.

Lubricants are some of the most important technical components of our daily life – and yet they are rarely noticed. And so it should be. After all, safety and progress can only be guaranteed by high-quality products with long service lives that invisibly keep our ever more dynamic world turning smoothly. LUKOIL Lubricants takes its responsibility as a manufacturer of first-class, reliable lubricants extremely seriously. The company's products are used across a range of industries, ensuring the smooth functioning of vehicles as well as boats and agricultural machinery.

In this way, LUKOIL helps keep today's highly complex logistics networks from grinding to a halt – which would be unthinkable in our modern ultramobile society. Nor is coming to a halt an option for the LUKOIL company. Stable growth, securing of resources and steady improvement of products and processes are essential in a highly dynamic market. LUKOIL has therefore established the goal of being at the absolute top in the most challenging segment: fully synthetic, high-performance oils for modern vehicle engines. The development of LUKOIL products for agricultural applications is an impressive and successful example of this strategy – but we are always striving for more.

Founded in 1991 by a merger of regional oil and gas transport companies in the western Siberian cities of Langepas, Uray and Kogalym (LUK), LUKOIL developed into the largest private oil group in Russia. In line with its established creed of vertical integration – in other words raw material extraction, production and development as well as sales of high-quality products all at a single company – LUKOIL always strives to offer perfect service to its customers. In recent years, the focus here has been on the lubricants business.







Through constant development work at seven refineries and production sites in Europe, including the newly added production and filling plant at the oil port of Lobau, LUKOIL Lubricants has already won over more than 300 manufacturers in the automotive industry, especially with the high-quality oils for the critical European market.

The Austrian market is also gaining in importance here. After all, it is from here that LUKOIL serves all Western European countries, not only with production and development, but also with the operation of a highly efficient distribution network. The lion's share of the value creation is therefore situated in Austria – at the heart of Europe. An important signal of stability and a long-term orientation. The decades of experience of Austrian experts in the role of a Central European hub and interface between East and West also ensure smooth functioning of all critical logistical flows. With the Danube port of Lobau and the Vienna Airport, high-capacity transport routes are a given.



LUKOIL AGRI

THE PREMIUM MOTOR OIL FROM LUKOIL IS PREPARING TO CONQUER THE EUROPEAN MARKET FROM VIENNA – WITH HIGH QUALITY AND A SUSTAINABLE BUSINESS MODEL.

Our LUKOIL products for agricultural applications were specially selected to optimally address the operational needs of your machinery. These products satisfy the highest performance requirements and protect YOUR agricultural machinery under all conditions and weather. This is why you should choose LUKOIL lubricants for the best protection of YOUR machinery.













QUALITY FROM AUSTRIA

In our state-of-the-art production facilities in Lobau, Vienna, as well as in Finland and Romania, we manufacture over 40,000 tonnes of lubricant every year, using first-class source materials. Our scientific experts also work continuously to improve our products to quarantee ever greater reliability and progress.

In this way, LUKOIL can supply customers around the world – even in the most demanding segment of fully synthetic, high-performance lubricants – with reliable and individual solutions for special applications.

IT'S A MATTER OF TRUST.

AVANTGARDE

UNIVERSAL OILS FOR AGRICULTURAL AND CONSTRUCTION MACHINERY

LUKOIL AVANTGARDE 10W



Prod. No.: 567510

SPECIFICATIONS

ACEA E2 API SF/CF/CF-2 **MAN** 270 MB 228.0 **MTU** Oil Category 1 **ZF** TE-ML 05K/ 21K

LUKOIL AVANTGARDE 20W-20



Prod. No.: 567520

SPECIFICATIONS

ACEA E2 API SF/CF/CF-2 **MAN** 270 **MB** 228.0 MTU Oil Category 1 **ZF** TE-ML 03A/ 07D

LUKOIL AVANTGARDE 30

Prod. No.: 567530

Prod. No.: 567820



APPROVALS	SPECIFICATIONS

ThyssenKrupp ACEA E2 **Industrial Solutions**

API SF/CF/CF-2 **MAN** 270 **MB** 228.0 MTU Oil Category 1 **ZF** TE-ML 03A/ 04A/ 04B/ 07D

- LUKOIL AVANTGARDE is a mineral, single-grade motor oil for diverse applications.
- Suitable for various engines, such as utility vehicle engines, manual transmissions, retarders, torque converters and hydraulic systems of agricultural and construction machinery
- Also suitable for the lubrication of air compressors
- Usable as a detergent compressor
- Suitable for use in heavy duty, charged diesel and petrol engines

LUKOIL AVANTGARDE ULTRA PLUS 10W-40



	Synthetic super-high-performance (SHPD) diesel
_	by manage super mg. perjermance (b. 11 b) areset
	motor oil for mixed vehicle fleets

- It is suitable for extended oil change intervals in utility vehicles and offers optimal wearing and corrosion protection as well as outstanding ageing resistance.
- It reduces the friction in the engine and lowers the fuel consumption.
- Usable year-round, even for older petrol and diesel passenger car engines without diesel particulate filter

APPROVALS

API SL/CI-4 **Cummins** CES 20078 **Deutz** DQC III-10 Mack EO-N **MAN** M 3275-1 MB-Approval 228.3 MTU Oil Category 2 Renault VI RLD-2 **VOLVO** VDS-3

SPECIFICATIONS

Caterpillar ECF-1-a/ECF-2 **Cummins** CES 20076/77 Global DHD-1 Mack EO-M Plus Renault VI RLD **ZF** TE-ML 03A/ 05K/ 07D/ 21K



LUKOIL AVANTGARDE EXTRA 15W-40



Prod. No.: 567915	APPROVALS	SPECIFICATIONS			
 High-performance diesel (HPD) multi-grade motor oil, ideally suited for a mixed vehicle fleet This oil features outstanding ageing resistance and a high cleaning capacity with respect to combustion residues and deposits Suitable for older petrol and diesel passenger car engines without diesel particulate filter 	API SI/ CH-4	Cummins CES 20076 Deutz DQC II Mack EO-M MAN M 271 Renault VI RLD VOLVO VDS-2 ZF TE-ML 03A/ 04P/ 07D			

LUKOIL AVANTGARDE ULTRA 15W-40

Prod. No.: 568321



■ Super-high-performance diesel (SHPD) multi-grade motor oil for mixed vehicle fleets and extended oil change intervals. Also suitable for diesel passenger car engines without diesel particulate filter

Ensures long oil change intervals as per manufacturer specifications API SL/ CI-4 Cummins CES 20078 Deutz DQC III-10 MB-Approval 228.3 MTU Oil Category 2

APPROVALS

ACEA E7
Caterpillar ECF-1-a/ECF-2
Cummins CES 20071/72/76/77
DAF
Detroit Diesel DFS 93K215
Mack EO-M Plus/EO-N
MAN M 3275-1
Renault VI RLD-2
VOLVO VDS-3
ZF TE-ML 03A/04P/07D

SPECIFICATIONS



AVANTGARDE

UNIVERSAL OILS FOR AGRICULTURAL AND CONSTRUCTION MACHINERY

LUKOIL AVANTGARDE PROFESSIONAL LA 10W-30



Prod. No.: 568356 APPROVALS SPECIFICATIONS

- Synthetic, low-ash utility vehicle oil for extremely strict emission limits, especially suited for utility vehicles with EURO V and VI engines with exhaust gas recirculation, SCR and particulate filter
- The low-SAPS additives used reliably protect the exhaust gas aftertreatment system and the environment
- Also usable for EURO 0 IV according to manufacturer specification

API SN/ CJ-4
Deutz DQC III-10 LA
Mack EO-O Premium Plus
MAN M 3575
MB-Approval 228.31
MTU Oil Category 2.1
Renault VI RLD-3
VOLVO VDS-4

ACEA E9 API SM Caterpillar ECF-1-a/ ECF-2/ECF-3 Cummins CES 20081 ZF TE-ML 05K/07D/ 21K

LUKOIL AVANTGARDE PROFESSIONAL LA 10W-40



Prod. No.: 568357 APPROVALS SPECIFICATIONS

- State-of-the-art additive technology guarantees the longest oil change intervals and protects engines and particulate filters, even under extreme conditions
- Synthetic, low-ash utility vehicle oil meets extremely strict emissions limits. The innovative formulation was specially developed for EURO V and EURO VI utility vehicle engines with EGR, SCR and particulate filter
- High-quality base oils in combination with low-ash additives make LUKOIL AVANTGARDE PROFESSIONAL LA 10W-40 the ideal product for the modern vehicle fleet
- Thanks to the low-SAPS additives used, the exhaust gas emissions are extremely low, reducing impact on the environment and prolonging the lifespan of the particulate filter

API CJ-4
Cummins CES 20081
Deutz DQC III-10 LA
Mack EO-O Premium Plus
MAN M 3575
MB-Approval 228.31
MTU Oil Category 2.1
Renault VI RLD-3
VOLVO VDS-4

ACEA E9 API SM/ SN Caterpillar ECF-1-a/ ECF-2/ ECF-3 Detroit Diesel DDC 93K218 ZF TE-ML 04P/ 05K/ 07D/ 21K

LUKOIL AVANTGARDE PROFESSIONAL LA 15W-40



- Synthetic, low-ash utility vehicle oil, designed for extremely strict emissions limits. Specially formulated for EURO V and EURO VI utility vehicle engines with particulate filter and/or SCR technology
- Motor oil for heavy duty engines of the newest generation with particulate filter and/or SCR technology

Prod. No.: 568358

- Thanks to the low-SAPS formulation, this product guarantees low exhaust gas emissions and maximum protection of the environment
- Enables the longest oil change intervals and reliable component protection for the engine

API SN/ CJ-4 Cummins CES 20081 Mack EO-O Premium Plus MAN M 3575 MB-Approval 228.31 MTU Oil Category 2.1 Renault VI RLD-3 VOLVO VDS-4

APPROVALS

ACEA E9 API SM Caterpillar ECF-3 Deutz DQC III-10 LA ZF TE-ML 04P/ 07D

SPECIFICATIONS



LUKOIL TRANSMISSION LS 80W-90

Prod. No.: 582515

Prod. No.: 582520

Prod. No.: 583220



APPROVALS SPECIFICATIONS ZF TE-ML 05C/ 12C/ 21C API GL-5 (ZF003406) ZF TE-ML 16E

transmissions, utility vehicles, tractors and construction machinery

Universal transmission oil with extremely stable viscosity for

Used for differentials with limited slip and heavily loaded axle

heavy loads in axle transmissions as per the manufacturer specifications LUKOIL TRANSMISSION LS 85W-90



APPROVALS	SPECIFICATIONS
ZF TE-ML 05C/12C/21C	API GL-5
(ZF003494)	ZF TE-ML 07A/ 08/ 16E

 Features state-of-the-art antiwear additives and a reliably constant coefficient of friction

LUKOIL TRANSMISSION B 80W-90



■ The mineral axle transmission oil is used primarily in utility vehicles for standard oil change intervals with maximum load-bearing capacity

Axle transmission oil with good ageing stability

- Offers optimal wearing and corrosion protection, ensures a long transmission lifespan
- Suitable for hypoid axle transmissions in utility vehicles and heavy machinery

SPECIFICATIONS

API GL-5 MAN 342 Typ M1 MB 235.0 MIL-L-2105D VOITH 3.325-339 VOLVO 97310

ZF TE-ML 07A/ 08/ 16B/ 17B/ 19B/ 21A

LUKOIL ATF

Prod. No.: 583315



The universal, partly synthetic automatic transmission oil was developed for both cars and trucks

■ Excellent viscosity and temperature behaviour

- Excellent ageing and foaming behaviour, very good flow properties at low temperatures and reliable protection against wear and corrosion
- Used as a power transmission medium in automatic transmissions of cars, buses and all-terrain vehicles

MAN 339 L1/V1/Z1 VOITH H55.6335.XX ZF-TE-ML 04D/14A (ZF001146)

APPROVALS

Allison C-4
Caterpillar TO-2
GM DEXRON® II-D/ III-G
MAN 339 Typ D/ F
MB 236.1
RBAS TE-ML 09
VOLVO 97340/ 97341
ZF TE-ML 11A/ 11B/ 17C

SPECIFICATIONS



WHICH ENGINE OIL DO I NEED?

Information on other vehicle brands can be found in the LUKOIL Oilfinder at www.lukoil-lubricants.eu or requested by email: technics.lubes@eu.lukoil.com


LUKOIL TRANSMISSION MP 80W-85



Prod. No.: 583010	
APPROVALS	SPECIFICATIONS
MB -Approval 235.1	API GL-4 ZF TE-ML 08/ 16A/ 17A/ 19A

- Mineral transmission oil with high pressure absorption capacity, primarily for manual transmissions
- Top manual transmission oil with good ageing stability and very high load-bearing capacity
- Ensures an extremely long transmission lifespan thanks to optimal wearing and corrosion protection additives
- Low pour point, low viscosity temperature dependence

LUKOIL TRANSMISSION MP 85W-90





APPROVALS	SPECIFICATIONS
MB -Approval 235.1	API GL-4
ZF TE-ML 16A/ 17A/ 19A	MIL -L-2105
(ZF003413)	ZF TE-ML 08

LUKOIL TRANSMISSION UNI 80W-90





APPROVALS





- High-performance universal transmission oil for manual transmissions and axle transmissions
- High ageing-resistance and long service periods
- Protects against wear and optimises the lifespan of the transmission

MAN 341 Typ Z2 MAN 342 M2 ZF TE-ML 02B/ 05A/ 12L/ 12M/ 16B/ 17H/ 19B/ 21A (ZF001768) API GL-4/-5 API MT-1 ARVIN MERITOR 076-D MAN 341 Typ E2 MB 235.0 MIL-PRF-2105E SAE J2360 Scania STO 1:0 ZF TE-ML 07A/08/16C/19C/21B









UNIVERSAL OILS FOR AGRICULTURAL AND CONSTRUCTION MACHINERY

LUKOIL VERSO MOTOR 10W-40



Prod. No.: 568240

APPROVALS

SPECIFICATIONS

ACEA E2

ZF TE-ML 06B/ 06F/ 07B (ZF001753)

Allison C-4
API SF/ CG-4/ GL-4
Caterpillar TO-2
Ford M2C 159B/ C
John Deere J27
Massey Ferguson M1139/ M1144/ M1145
MB 227.1/ 228.1
ZF TE-ML 06A/ 06C/ 06Q/ 06R

- High-quality super tractor universal oil (STOU) for yearround use in engines, hydraulic systems and transmissions with wet brakes in agricultural equipment and construction machinery
- Outstanding ageing-resistance
- High cleaning capacity with respect to combustion residues and deposits

LUKOIL VERSO MOTOR 15W-40



Prod. No.: 568230

SPECIFICATIONS

ACEA E2 Allison C-4 API SF/ CF-4/ GL-4 Caterpillar TO-2 Ford M2C 159-B John Deere JDM J27 Massey Ferguson M1144/ CMS M1145 MB 228.1 MIL-L-2104D ZF TE-ML 06B/ 06F/ 07B

LUKOIL VERSO MOTOR 15W-30



Prod. No.: 568225

SPECIFICATIONS

ACEA E2

Allison C-4 API SF/CF-4/GL-4 Case NEW HOLLAND CNH MAT3525 Case Steyr NEW HOLLAND CVX/ CVT/ TVT Caterpillar TO-2 DEUTZ-FAHR **FENDT** Ford M2C 159-B/ 259-C John Deere JDM J27 LINDNER Geotrac Serie 4 MB 228.1 Massey Ferguson M1139/M1144/M1145 MIL-L-2104D **NEW HOLLAND** 324G **STEYR** 9000 **VALTRA ZF** S-MATIC



PACKAGING INFORMATION

PACKAGING	TARE BOX (KG)	TARA CONTAINER (KG)	WIDTH (MM)	HÖHE (MM)	LENGTH (MM)	DIA- METER (MM)	UNITS PER PALLET	PALLET SIZE (CM)	UNITS PER SALE UNIT
1 LITRE BOTTLE	0,35	0,08	260	240	380	-	432	120 x 80	12
5 LITRE BOTTLE	0,32	0,3	260	330	380	_	81	120 x 80	3
20 LITRE CANISTER	-	1,0	260	362	300	-	36	120 x 80	-
DRUM 60 LITRES	-	4,0	-	586	-	384	6	120 x 80	-
DRUM 205 LITRES	-	14,5	-	878	-	585	4	120 x 120	-
IBC CONTAINER 1000 LITRES	-	60	1000	1200	1200	-	-	-	-



UNIVERSAL OILS FOR AGRICULTURAL AND CONSTRUCTION MACHINERY

LUKOIL VERSO HGN



Prod. No.: 583410 SPECIFICATIONS

- Universal oil for construction machinery, agricultural equipment and tractors with combined lubrication system for hydraulics, transmission and wet brakes (UTTO)
- Ensures fault-free operation of wet brakes and clutches
- Outstanding ageing-resistance
- Viscosity class SAE 15W-30 or SAE 80W

API GL-4 Case NEW HOLLAND CNH MAT 3525 DIN 51502-HVLPD FORD ESN-M2C86-B Massey Ferguson CMS M1135

LUKOIL VERSO LVX



Prod. No.: 583420 APPROVALS SPECIFICATIONS

- Universal oil for heavy machinery and tractors with combined lubrication system for hydraulics, transmission and wet brakes (UTTO)
- Ensures fault-free operation of wet brakes and clutches
- Viscosity class SAE 10W-30 or SAE 75W-80

ZF TE-ML 03E/05F/ 17E/21F (ZF002303) Allison C-4 API GL-4 **CASE** MS 1207/1210 Caterpillar TO-2 **CNH** MAT 3505/3509/3525 FORD ESN-M2C134-D/ M2C86-C/M2C86-B FORD NEW HOLLAND FNHA-2-C-200.00/201.00 John Deere JDM J20C/D KUBOTA UDT LANDINI MACROS/C Massey Ferguson CMS M1135/ M1141/M1143/M1145 **NH** 410B Valtra G2-08 **VOLVO** VCE WB 101 (97303) **ZF** TE-ML 06K

LUKOIL VERSO STE



Prod. No.: 583440 SPECIFICATIONS

- Specially developed universal oil for hydraulics and wet brakes for KALMAR forklifts
- Prevents stick-slip
- Viscosity class ISO-VG 46 or SAE 20

API GL-4

LUKOIL VERSO NPS



- Prod. No.: 583450 SPECIFICATIONS
- Universal oil for construction machinery and tractors with combined lubrication system for hydraulics, transmission and wet brakes
- Specially developed for optimising the noise behaviour of loud wet brakes
- Viscosity class SAE 15W-30

API GL-4



LUKOIL GEYSER ST 22



Prod. No.: 572520

APPROVALS

DANIELI, GMS GROUP, KVANTA, PALFINGER, SN (SMS GROUP), SULZER PUMPS, TMT, VOITH

LUKOIL GEYSER ST 32



APPROVALS

Bosch Rexroth 90220/ RD90220, DANIELI, Duplomatic, FURUKAWA, GMS GROUP, Kopex Machinery, KVANTA, PALFINGER, PARKER DENISON HF-0/-1/ -2, SMT Scharf, SN (SMS GROUP), Sulzer Pumps, Thyssenkrupp, TMT, VOITH Turbo

SPECIFICATIONS

AIST 126/127 **ASTM** D6158-HM Cincinnati P68/P69/P70-HM **DIN** 51524-2-HLP Eaton E-FDGN-TB002-E/ **Brochure** 03-401-2010 Eaton Vickers 1-286-S Fives P68/ P69/ P70-HM GB 11118.1-2011 GM LS-2 ISO 11158-HM/ 6743-4-HM JCMAS P041 HK MAG Cincinnati Machine P-70 MAG P68/ P69/ P70-HM **SAE** MS 1004

Failure load stagee **DIN ISO** 14635-1 A/ 8,3/ 90-M:>10 SEB 181222 **US Steel** 127/136 VDMA 24318-HLP

LUKOIL GEYSER ST 46/68: ZF TE-ML 07H

- hydraulic oil with advanced additive technology
- Excellently suited for use in hydraulic drives, lifting
- Optimal wearing and



LUKOIL GEYSER ST 46

Prod. No.: 572540

APPROVALS

ALTA, Automa, Battenfeld, Bosch Rexroth 90220/ RD 90220, **DANIELI** 0.000.001, **Duplomatic**, Eickhoff, Engel, FELUWA Pumpen, Ferrit, FLSmidth MAAG, GMS GROUP, HUSKY HS 207, HYDAC International, Kopex Machinery, Krauss Maffei Berstorff, KVANTA, LAEIS, LOESCHE, PALFINGER, PARKER DENISON HF-0/-1/-2, SCHARF SMT, SMS Siemag, SN (SMS GROUP), Sulzer Pumps, Thyssenkrupp, TMT, UNILOY/ MILACRON, VOITH Turbo


LUKOIL GEYSER ST 68



APPROVALS







corrosion protection, rapid air release capacity



HYDRAULIC OILS FOR UTILITY VEHICLES

LUKOIL GEYSER ZF 46

advanced additive technology.

Prod. No.: 572546



High-quality, zinc-free mineral hydraulic oil with

For use in hydraulic systems for which "ash-free" hydraulic oils are specified as well as in screw compressors.

Optimal wearing and corrosion protection, rapid air release capacity and low foaming tendency.

APPROVALS

ALTA Automa Bosch Rexroth RD 90220 **Danieli** 0.000.001 Kraus Maffei **MAG Cincinnati** Machine P-70 PARKER DENISON

HF-0/-1/-2 Siemens **SN** (SMS GROUP) Sulzer Pumps **WOOJIN PLAIMM**

ASTM D6158 HM **DIN** 51524-2 (HLP) **Eaton Vickers** M-2950-S GM LS-2 ISO 20763 **SAE** MS 1004 Failure load stage DIN ISO 14635-1 A/8,3/90-M:>10

LUKOIL GEYSER M 32

Prod. No.: 572630



SPECIFICATIONS

AIST 126/127 **ASTM** D6158-HV Bosch Rexroth RD 90220/ RDE 90235

Cincinnati P68/ P69/ P70 **DIN** 51524-3 HVLP Eaton E-FDGN-TB002-E **Brochure** 03-401-2010 Fives P68, P69, P70-HV

GB 11118.1-2011 GM LS-2 ISO 11158-HV/ 6743-4 HV

JCMAS PO41 HK PARKER DENISON

HF-0/-1/-2 **SAE** MS 1004-HV Failure load stage DIN ISO 14635-1 A/8,3/90-M:>10 SEB 181222

US Steel 126/127 **VDMA** 24318 - HVLP ZF TE-ML 07H



LUKOIL GEYSER M 46


Prod. No.: 572640

LUKOIL GEYSER M 68

Prod. No.: 572680



PALFINGER



- Used in hydraulic drives that are subject to large fluctuations in ambient temperature
- The balanced formulation offers optimal wearing and corrosion protection, rapid air release capacity and low foaming tendency



LUKOIL



LUKOIL GEYSER BIO S 32





High-quality, zinc-free, rapidly biodegrading hydraulic oil based on saturated, synthetic esters and advanced additive technology

- Excellently suited for year-round use in heavy duty hydraulic systems for construction, agricultural and forestry machinery, mobile equipment and water treatment plants
- The balanced, low-ash formulation is the basis for maximum oil change intervals and offers optimal wearing and corrosion protection, good air release capacity and low foaming tendency along with the lowest possible environmental impact

LUKOIL GEYSER BIO S 46



Prod. No.: 572693

 PALFINGER
 ON C 1158: >90 %

 ON C 2027 - HEES

 VDMA 24568 - HEES

LUKOIL CHAIN MEDIUM



Prod. No.: 580428

LUKOIL CHAIN HEAVY

Prod. No.: 580429

APPROVALS

Thyssenkrupp

- Special lubrication oil with good clinging properties for use in the wood processing and saw industry
- Lubrication of chains, conveyors and transport equipment as well as slideways and guideways on wood processing machinery
- Prolonged lifespan thanks to reduced wear, lowers lubricant consumption and maintenance requirements, does not resinify
- Protects against rust, corrosion and moisture

LUKOIL BIOCHAIN LIGHT

MEDIUM

HEAVY

Prod. No.: 580431

Prod. No.: 580481

Prod. No.: 580432

Prod. No.: 580433



- Biologically degradable open-system lubrication oils based on rapeseed oil
- Good clinging capacity, reliable friction reduction, good wearing protection, economical consumption
- Ideally suited for use in open lubrication systems in the wood processing and saw industry
- Good low temperature behaviour

LUKOIL BIOSEGAROL E 100



 Rapidly biodegrading, environmentally friendly chainsaw oil based on high-quality rapeseed oil

- Reliable wearing and corrosion protection as well as good clinging capacity
- Clings even under cold and damp conditions
- Optimal lubrication of the chain links

SPECIFICATIONS

ON C 2030 Biodegradable after 21 days as per ON C 1158: > 90 %

LUKOIL LUBRICANTS EUROPE GmbH

1220 Vienna, Uferstrasse 8 www.lukoil-lubricants.eu Version: 1.0, November 2019

MORE INFORMATION AVAILABLE FROM:

AUSTRIA

Automotive: Telephone 0810 959 8884 info.schmierstoffe-automotive@eu.lukoil.com Industry: Telephone 0810 959 8886 info.schmierstoffe-industry@eu.lukoil.com Dealer: Telephone 0810 959 8885 info.schmierstoffe-dealer@eu.lukoil.com

GERMANY

Automotive: Telephone 01806 06 00 004 info.schmierstoffe-automotive@eu.lukoil.com Industry: Telephone 01806 06 00 006 info.schmierstoffe-industry@eu.lukoil.com Dealer: Telephone 01806 06 00 005 info.schmierstoffe-dealer@eu.lukoil.com

CZECH REPUBLIC

Telephone 844 900 033 info.lubes-CEE@eu.lukoil.com

HUNGARY

Telephone 0680 980 975 info.lubes-CEE@eu.lukoil.com

SLOVAKIA

Telephone 0850 166 670 info.lubes-CEE@eu.lukoil.com

ITALY

Telephone +43 1 205 222 8007 info.lubes-CEE@eu.lukoil.com

SWEDEN





WWW.LUKOIL-LUBRICANTS.EU